

✓ SOFT FEELING

✓ HIGH ABSORPTION RATE

FLAIR UPR // Flair without borders



INDOOR



ANTI-SLIP



ABSORBING

SPECIFICATIONS

MANUFACTURING PROCESS

FABRICAGEMETHODE | TECHNIQUE DE FABRICATION | HERSTELLUNGSART

TUFT, 1/8" CUT-PILE

PILE COMPOSITION

POOLSAMENSTELLING | NATURE DU VELOURS | POLMATERIAL

100% PA SOFT HEAT-SET

BACKING

RUGTYPE | ENVERS | RÜCKEN

BLACK ELASTO-FLEX-VINYL (UPR)

PILE WEIGHT

POOLINZETGEWICHT | POIDS MIS EN ŒUVRE | POLEINSATZGEWICHT

± 600 GR/M²

PILE HEIGHT

POOLHOOGTE | HAUTEUR DU VELOURS | POLHÖHE

± 5 MM

FINISHING

AFWERKING | FINITION | FERTIGUNG

FINISHED WITHOUT VINYL BORDERS

(OPTICAL BORDERS POSSIBLE)

WASHABLE

WASBAAR | LAVABLE | WASCHBAR



COLOURS & DESIGN

KLEUREN & DESSIN | COULEURS & DESSIN | FARBEN & ENTWURF

ANY DESIGN, ANY COLOUR POSSIBLE

(WITH PREFERENCE PANTONE-REFS)



SIZES

MATS & CARPETS - RECTANGLE (IN CM)

39x58 | 50x75 | 50x120 | 50x150 | 67x120 | 67x150 | 67x170 | 100x150 | 100x200 | 200x150

OTHER SHAPES & SIZES


UPON DEMAND; ALL WITHIN 200 CM WIDTH AND 20 LM



SIDEVIEW



BACKING



PILE TEXTURE

