

✓ LUXURIOUS LOOK & FEEL

✓ GOOD CHOICE FOR RUGS

DECOLUX UPrx // Decolux without borders



INDOOR



ANTI-SLIP



ABSORBING

SPECIFICATIONS

MANUFACTURING PROCESS

FABRICAGEMETHODE | TECHNIQUE DE FABRICATION | HERSTELLUNGSART

TUFT, 1/8" CUT-PILE

PILE COMPOSITION

POOLSAMENSTELLING | NATURE DU VELOURS | POLMATERIAL

100% PA HEAT-SET

BACKING

RUGTYPE | ENVERS | RÜCKEN

BLACK ELASTO-FLEX-VINYL (UPrx)

PILE WEIGHT

POOLINZETGEWICHT | POIDS MIS EN ŒUVRE | POLEINSATZGEWICHT

± 900 GR/M²

PILE HEIGHT

POOLHOOGTE | HAUTEUR DU VELOURS | POLHÖHE

± 7 MM

FINISHING

AFWERKING | FINITION | FERTIGUNG

FINISHED WITHOUT VINYL BORDERS

(OPTICAL BORDERS POSSIBLE)

WASHABLE

WASBAAR | LAVABLE | WASCHBAR

30°



COLOURS & DESIGN

KLEUREN & DESSIN | COULEURS & DESSIN | FARBEN & ENTWURF

ANY DESIGN, ANY COLOUR POSSIBLE

(WITH PREFERENCE PANTONE-REFS)



SIZES

MATS & CARPETS - RECTANGLE (IN CM)

67X150 | 67X170 | 100X150 | 100X200 | 200X150

OTHER SHAPES & SIZES

UPON DEMAND; ALL WITHIN 210 CM WIDTH AND 20 LM



SIDEVIEW



BACKING



PILE TEXTURE

